



Motor Oil & Lubricants

REXOIL DIAMOND PRO FE 5W/30 SN/CF

REXOIL DIAMOND PRO FE 5W/30 is full synthetic engine oil for new generation engines which is developed with high performance additives and synthetic base oils. It is made with a proprietary blend of leading edge components formulated to be fully compatible with the latest Diesel Particulate Filters (DPF's) and Gasoline Catalytic Converters (CAT's). Helps to reduce particulate build up in Diesel Particulate Filters and reduce deposits and sludge build-up to enable long and clean engine life.

Properties

- It has a low sulfur and phosphorus content.
- Provides high resistance to tear due to high viscosity index.
- Keeps the engine's most sensitive parts clean thanks to its advanced detergent and dispersive additives.
- Helps to reduce particulate build up in Diesel Particulate Filters.
- Helps to reduce poisoning of Gasoline Catalytic Converters.
- Satisfies the most demanding manufacturer service plans by permitting extra-long oil change intervals.
- Provides superior performance under extreme cold start up conditions.

Existing OEM Approvals

- Volkswagen VW50400
- Volkswagen VW50700
- MB-Approval 229.51

Approvals and Specifications

- API SN / API SM / API SL
- API CF
- ACEA C3-08 / C3-10
- MB-Approval 229.51
- Volkswagen VW50400
- Volkswagen VW50700
- BMW Longlife-04
- Porsche C30



Motor Oil & Lubricants

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	9,3 - 12,5
Viscosity Index	ASTM D2270	Min. 150
Flash Point, °C	ASTM D92	Min. 200
Pour Point, °C	ASTM D97	Max. -36
Total Base Number, mg KOH/g	ASTM D 2896	Min. 7,5