

# SHINE OIL S-6

**REXOIL SHINE OIL S-6** is white process oil which has paraffinic structure, formulated with high quality products for wide range of applications. **REXOIL SHINE OIL S-6** has very good color and oxidation stability. Also have a wide range of viscosities for different purpose usage.

## Area of Use

Plastic, rubber, chemical, agriculture, paper, textile industry, in particular skin oil, wax, ink and paint manufacturing, foam cutting, and also are used as raw materials in industrial lubricants.

## Technical Properties

| Test                              | Method     | Typical Properties |
|-----------------------------------|------------|--------------------|
| Kinematic Viscosity (100°C) [cSt] | ASTM D445  | 5,7 – 6,4          |
| Viscosity Index                   | ASTM D2270 | Min. 126           |
| Flash Point, °C                   | ASTM D92   | Min. 226           |
| Pour Point, °C                    | ASTM D97   | Max. -15           |
| Color (ASTM)                      | ASTM D1500 | L0,5               |
| Color (Saybolt)                   | ASTM D156  | +30                |
| <b>Carbon Distribution</b>        |            |                    |
| % aromatic                        | ASTM D3238 | 0,0                |
| % naphthenic                      | ASTM D3238 | 17,4               |
| % paraffinic                      | ASTM D3238 | 82,6               |