



Motor Oil & Lubricants

EVO PLUS

20W/50 CF-4/SJ

EVO PLUS 20W/50 is manufactured with high quality mineral base oils and advanced performance additives for cars and light commercial vehicles working by diesel fuel which can be used confidence in all four seasons. It is suitable for working under particularly difficult conditions and frequently stops and goes live vehicles. Also safely used for lubrication in light trucks, minibuses, vans, other four-stroke engines and other construction and agricultural machines. It can be also used in some vehicles running on fuels such as gasoline and LPG.

Properties

- Provides easily the first work at low temperatures by its excellent viscosity.
- Its high oxidation stability feature provides its protection until the next oil change.
- It has a high resistance to tear due to the high viscosity index property.
- Extends oil change intervals even at high sulfur fuel use.

Approvals and Specifications

- API CF-4/SJ
- ACEA A3/B3-04
- Mack EO-L Plus
- MTU Level 1
- Volvo VDS
- MB 228.1, 229.1
- ACEA E3-96 Issue 4
- MAN 271
- Deutz DQC-I-05

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	16,3 – 21,9
Viscosity Index	ASTM D2270	Min. 115
Flash Point, °C	ASTM D92	Min. 235
Pour Point, °C	ASTM D97	Max. -23
Total Base Number, mg KOH/g	ASTM D2896	Min. 7,0